

## KABOLA ELECTRICAL BOILERS

30, 40 or 50 liters, for horizontal mounting



TYPE	30BEL	40BEL	50BEL
content	30 liters	40 liters	50 liters
working pressure	0,6MPa	0,6MPa	0,6MPa
height with supports	470mm	470mm	470mm
width	450mm	450mm	450mm
total depth	450mm	525mm	590mm
power	800W	800W	800W
voltage	230V / 50Hz	230V / 50Hz	230V / 50Hz
IP value	IPX1	IPX1	IPX1
connections	1/2"	1/2"	1/2"
warm-up time 10-85 °C	~210 min	~290 min	~360 min

These boilers have been specially developed for use on boats. Electric element and tank are made of high-quality stainless steel 316, so that pure water is always supplied. Outer sheath and fixing brackets are made of stainless steel 304.

Thermal insulation and exterior cladding are ecologically responsible and fully comply with all required application conditions prescribed for this product.

We offer a 5-year warranty on the tank and the electric element.

contact: info@kabola.nl phone +31 (0) 347 320 030











WWW.KABOLA.NL



## KABOLA ELECTRICAL BOILERS WITH HEAT EXCHANGER CONNECTION

40, 50, 80, 100 or 120 liters, for horizontal mounting



TYPE	40BTG	50BTG	80BTG	100BTG	120BTG
content	40 liters	50 liters	80 liters	100 liters	120 liters
working pressure	0,6MPa	0,6MPa	0,6MPa	0,6MPa	0,6MPa
height with supports	470mm	470mm	470mm	470mm	470mm
width	450mm	450mm	450mm	450mm	450mm
total depth	525mm	590mm	850mm	1015mm	1130mm
power	800W	800W	800W	800W	800W
voltage	230V/50Hz	230V/50Hz	230V/50Hz	30V/50Hz	30V/50Hz
IP value	IPX1	IPX1	IPX1	IPX1	IPX1
connections	1/2"	1/2"	1/2"	1/2"	1/2"
warm-up time 10-85 °C	~290 min	~360 min	~580 min	~720 min	~870 min

These boilers have been specially developed for use on boats and can also be connected to the cooling water. The heat exchanger, electric element and tank are made of high-quality stainless steel 316, so that pure water is always supplied. Outer casing and mounting brackets are made of stainless steel 304. Connection option for an additional electric thermostat is standard.

Thermal insulation and exterior cladding are ecologically sound and fully comply with all required application conditions prescribed for this product.

We offer a 5-year warranty on the tank and the electrical element.

contact: info@kabola.nl phone +31 (0) 347 320 030











WWW.KABOLA.NL