KABOLA heating systems

ECOTERM
ELECTRIC UNDERFLOOR HEATING

Low voltage underfloor heating for travelhome trailers



SYSTEM SPECS

- Low initial investment
- No maintenance costs
- Extremely low consumption
- Long lifespan
- Space-saving (no radiators and pipes).
- Even heat distribution
- Easy installation

This electric underfloor heating is ideal for combining with existing electric solar panels and yet to be installed.





FLAT STRIP
LOW VOLTAGE
UNDERFLOOR HEATING

ECOTERM
ELECTRIC UNDERFLOOR HEATING

BASIC FEATURES

Save space
There are no physical obstacles in rooms such as radiators, pipes, etc.

No maintenance costs
There are no maintenance costs due to the extremely durable properties of heating strips long-term resistance to mechanical loads. Very reliable electronics guarantee a long lifespan.

Safe and certified
Safety is guaranteed by high-quality, reliable construction of heating strips
and installation according to construction standards. The complete system is safety certified.

Optimal temperature distribution
Lower body at higher temperatures than the head. Evenly distributed temperature over the floor and the surface of the room, as well as heat transfer. Large heating surface (entire floor area).

Ecology
Less dust, fewer mites, fewer bacteria. Increased hygiene in the room, less allergens.
No noise, unpleasant odors and dust circulation.

TECHNICAL PROPERTIES

System power supply
Power supply: 230 V / 50 Hz Heating supply: 5V-40V / 50 Hz
Temperature
Heating strips up to 40 °C. Floor up to 28 °C ideal temperature profile.
Method of installation and application:
Underfloor or wall heating. Application: homes, catering establishments, business premises, halls, etc.
Guarantee
For electronics 5 years. For heating strips 20 years.
Safety
According to regulations and CE certificate
Heating element
Aluminum foil, insulated on both sides with polypropylene, mechanically and chemically resistant

- Low consumption and extremely low energy transmission losses.
- Efficient use of energy in the lower part of the room.
- No transmission losses as with other systems.
- It has an optimal temperature profile and operating mode.
- Savings in consumption compared to other systems of at least 25%.

MONTHLY CONSUMPTION WITH WELL APPLIED THERMAL INSULATION; INDICATIVE 75 W/m2

Monthly heating consumption for 60 m2 is 460 kWh.
Even more savings are possible with a nightly rate

Monthly maintenance € 0.00

Low voltage underfloor heating: ideal for travelhome trailers

INSTALLATION METHOD

Installation can be done under all types of floor coverings.
The heating strip is installed in the floor: Styrofoam or PIR panels (at least 5 cm) are mounted on the basic floor. *Reflective aluminum foil is applied UNDER the Styrofoam or use PIR panels with one side cached aluminium layer, to be positioned at the bottom side. This to avoid current leaks*.
The heating strips are placed / taped on the panels. We advise to place facade mesh on which a cast floor can be applied. When applying ceramic tiles, laminate, PVC or wood use a thin layer of Styrofoam between the underfloor heating and your choice top finish.

ECOTERM, cheap for 4-12 square meters!!!







Simple system configuration Eco friendly - Sealed - 24/7 Support

COMPONENTS

Control unit: Wi-Fi Thermostat
Wi-Fi thermostat (the most modern way of control, the control is controlled via the internet, i.e. with your phone.
Option: can also be linked to our Kabola Zone Scheme. Please inquire for this option.

Custom part: Distribution box
The distribution box built into the wall contains a soft start and a transformer (one or more). We use a toroidal transformer, which has small energy transmission losses compared to a classical transformer.

Heating element: Aluminium strips
Aluminium strip that is heated by the current. This is generated by a secondary transformer, which has a safe low voltage.

FLAT STRIP
LOW VOLTAGE
UNDERFLOOR HEATING

ECOTERM
ELECTRIC UNDERFLOOR HEATING

Kabola Zone control system in combination with ECOTERM underfloor heating

5 inch, 3 zone display for horse truck or trailer

Website based control on smartphone

1

Zone 1 bathroom

Zone 2 living room

Zone 3 bedroom

Kabola NMEA2000 heating controller

Low voltage transformer 5V-40V / 50 Hz

Zone 1 (bathroom)

Zone 2 (living room)

Zone 3 (bedroom)

Low voltage transformer 5V-40V / 50 Hz



IDEAL TEMPERATURE PROFILE:

CEILING TEMPERATURE 20 °C
HEAD TEMPERATURE 21 °C
HAND TEMPERATURE 22 °C
FOOT TEMPERATURE 23 °C

Please check out our explanation video on Vimeo

FLAT STRIP
LOW VOLTAGE
UNDERFLOOR HEATING

ECOTERM
ELECTRIC UNDERFLOOR HEATING

Manual

Technical manual installation underfloor heating



Installation and dimensions for the underfloor heating strip:
From the wall-mounted transformer cabinet, mount 1 connection cable at the beginning of the conductor strip with the necessary stainless steel screws, washers, bolts and aluminum contact strips.

Always place the conductor strip at 15 cm from the walls, so that after 2 or 3 lengths along the wall the tape can be folded back to lay parallel to the first laid track. Make sure that these 2 strips are 10 cm apart. Always keep a distance of 15 cm from the wall at the folding points.

In this way, fill the entire floor space until the end point of the conductor strip ends up under the transformer cabinet again. Here you cut the strip sufficiently, fold it also between the aluminum contact strips of the connection strip and use it to mount the second connection cable.
PLEASE NOTE! There may be differences per project.

KABOLA heating systems

ECOTERM ELECTRIC UNDERFLOOR HEATING

Sample package technical information

Technical description (class C insulation)

Space (floor per m2)	Needed power (W/m2)	Total power (W)	Fused ampere (C-characteristics)	Amount of transformers and sizes	Maximum consumption per heating season (kWh)	Consumption per month (kWh)	Standard Wi-Fi thermostat (pieces)
25 -30	70 -80	2.300	16A	300x450x120mm (1 trafo)	2.000	350	1
50 -60	70 -80	4.300	2x16A	500x600x120mm (2 trafos)	3.250	540	1
70 -90	70 -80	6.000	2x20A	500x600x120mm (2 trafos)	4.300	720	1
90 -100	70 -80	9.000	3x20A	800x650x120mm (3 trafos)	6.000	1.000	1

*The target price per m2 is **€ 55,- excl. vat***

Prices are valid for 2024, excl. vat

* ***One heating season exists of 6 months***

* ***Consumption data are indicative for cold months (Dec, Jan, Feb)***

Technical properties

- **System power supply:**
  power supply: 230 V / 50 Hz
  heating supply: 5V -40V / 50 Hz (low voltage)
- **Temperature:** heating strips up to 40°C. Floor up to 28°C ideal temperature profile.
- **Method of installation and application:** underfloor or wall heating.
  Application: homes, catering establishments, business premises, halls, etc.
- **Warranty:** 5 years for electronics. For heating strips 20 years.
- **Safety:** according to regulations and CE certificate

OPERATION

The desired temperature is set on the thermostat (or on the WiFi thermostat).
If the set temperature is higher than the room temperature, the transformer is switched on via soft start and current flows via the transformer through the aluminum strip in the subfloor.
This is the heating element and therefore the heater.
The aluminum strip, and thus the layer above the strip, is heated (heat rises) until the set temperature is reached. Then the system shuts down.
The essence of the saving is that the bottom plate accumulates (stores) thermal energy, so that the accumulation of energy can occur mainly at night, i.e. during a period when electricity is cheaper.
Ideal when you want to limit aditional floor height, when underfloor heating is applied.

This electric underfloor heating is ideal for combining with existing and future electric solar panels. No obstacles (radiators) in the space and equal heating distribution.

ECOTERM ELECTRIC UNDERFLOOR HEATING COMBINED WITH CINI ELECTRIC DESIGN RADIATORS

ECOTERM ELECTRIC UNDERFLOOR HEATING

Modern design and multifunctionality

CINI Electric Design Radiators

Finesse D is a decorative element with a simple and elegant design and multifunctional with the optional towel holders. For extra energy saving in the pre winter and post winter period choose for extra CINI Electric Design Radiators. Heating up quickly the used room.
In those periods you don't need to switch on the Ecoterm underfloor heating, since underfloor heating increases the room temperature at a lower speed.

Powder coated colors

RAL 9016	white
RAL 1013	ivory
RAL 9006	metallic grey
RAL 9005	black
RAL 1036	metallic gold

Optional towel holders

Decorative towel holder and dryer for bathroom, kitchen and toilet

- in color or polished stainless steel
- radiator height 600/800/1000 mm: 2 holders
- radiator height 1200/1500 mm: 3 holders



Sizes and properties

type	sizes HxB (mm)	thermal power (W)
FNE D06	600x408	400
FNE D08	800x408	500
FNE D10	1000x408	700
FNE D12	1200x408	900
FNE D15	1500x408	1200

Further technical information at request.

electrical heater











ECOTERM ELECTRIC UNDERFLOOR HEATING COMBINED WITH CINI ELECTRIC DESIGN RADIATORS

ECOTERM
ELECTRIC UNDERFLOOR HEATING

SIMPLE AND COMFORTABLE USE

Smart regulation - precise regulation of room temperature with the help of a digital thermostat

Temperature range 5-30 °C

Maintenance of the set temperature ± 0.5 °C

Digital thermostat

HIGH QUALITY

The construction of extruded aluminum profiles and stainless steel enables long-term stability of the product over time.

5 year warranty

QUICK HEATING AND SAFETY

Finesa D is a dry radiator, with an integrated electric heater, without the presence of a heating fluid. The heat is transferred very quickly and evenly from the heaters to the front panels. The dry heating system enables safe operation of the device, without the possibility of freezing or increasing the pressure inside the heating body.

Additional modes:
frost protection mode, overheating protection mode

High security

Overheating protection

Freezing protection

IP PROTECTION

Protection from spraying water from all directions

IPX4 protection

KABOLA heating systems

KABOLA HEATING SYSTEMS Ltd.
Placotiweg 1E
4131 NL Vianen
Netherlands

+31 (0)347 320 030
info@kabola.nl
www.kabola.nl